



UL Product iQ
UL'S NEXT GENERATION CERTIFICATIONS SEARCH
 The same trusted data in a modern search engine.

**NOW
 AVAILABLE**

▶ LEARN MORE

ZODZ2.E197662
Positioning Devices - Component

[Page Bottom](#)

Positioning Devices - Component

[See General Information for Positioning Devices - Component](#)

ARNOCANALI S P A

E197662

VIA G DI VITTORIO 34/36

RIGNANO SULL'ARNO


50067 FLORENCE, FI ITALY

Positioning Devices Investigated to ANSI/UL 1565

| Catalog No. | Maximum Use Temp °C(°F) |
|--|-------------------------|
| PC/ABS Wiring Ducts (grey color) | |
| V6H 100100 | 65 (149) |
| V6H 2540 | 65 (149) |
| V6H 2625 | 65 (149) |
| V6H 40100 | 65 (149) |
| V6H 4025 | 65 (149) |
| V6H 4040 | 65 (149) |
| V6H 4060 | 65 (149) |
| V6H 4080 | 65 (149) |
| V6H 60100 | 65 (149) |
| V6H 60120 | 65 (149) |
| V6H 6025 | 65 (149) |
| V6H 6040 | 65 (149) |
| V6H 6060 | 65 (149) |
| V6H 6080 | 65 (149) |
| V6H 80100 | 65 (149) |
| V6H 80120 | 65 (149) |
| V6H 8025 | 65 (149) |
| V6H 8040 | 65 (149) |
| V6H 8060 | 65 (149) |
| V6H 8080 | 65 (149) |
| Plastic Wiring Ducts (grey color) | |
| V5K 100100 | 50 (122) |
| V5K 10030 | 50 (122) |
| V5K 10040 | 50 (122) |
| V5K 10060 | 50 (122) |
| V5K 10080 | 50 (122) |

| | |
|-------------------|----------|
| V5K 2525 | 50 (122) |
| V5K 2540 | 50 (122) |
| V5K 2580 | 50 (122) |
| V5K 40100 | 50 (122) |
| V5K 4025 | 50 (122) |
| V5K 4030 | 50 (122) |
| V5K 4040 | 50 (122) |
| V5K 4060 | 50 (122) |
| V5K 4080 | 50 (122) |
| V5K 60100 | 50 (122) |
| V5K 60120 | 50 (122) |
| V5K 6025 | 50 (122) |
| V5K 6030 | 50 (122) |
| V5K 6040 | 50 (122) |
| V5K 6060 | 50 (122) |
| V5K 6080 | 50 (122) |
| V5K 80100 | 50 (122) |
| V5K 80120 | 50 (122) |
| V5K 8025 | 50 (122) |
| V5K 8030 | 50 (122) |
| V5K 8040 | 50 (122) |
| V5K 8060 | 50 (122) |
| V5K 8080 | 50 (122) |
| V6K 100100 | 50 (122) |
| V6K 10030 | 50 (122) |
| V6K 10040 | 50 (122) |
| V6K 10060 | 50 (122) |
| V6K 10080 | 50 (122) |
| V6K 2525 | 50 (122) |
| V6K 2540 | 50 (122) |
| V6K 2580 | 50 (122) |
| V6K 40100 | 50 (122) |
| V6K 4025 | 50 (122) |
| V6K 4030 | 50 (122) |
| V6K 4040 | 50 (122) |
| V6K 4060 | 50 (122) |
| V6K 4080 | 50 (122) |
| V6K 60100 | 50 (122) |
| V6K 60120 | 50 (122) |
| V6K 6025 | 50 (122) |
| V6K 6030 | 50 (122) |
| V6K 6040 | 50 (122) |
| V6K 6060 | 50 (122) |
| V6K 6080 | 50 (122) |
| V6K 80100 | 50 (122) |
| V6K 80120 | 50 (122) |

| | |
|--------------------------------------|----------|
| V6K 8025 | 50 (122) |
| V6K 8030 | 50 (122) |
| V6K 8040 | 50 (122) |
| V6K 8060 | 50 (122) |
| V6K 8080 | 50 (122) |
| PVC Wiring Ducts (all colors) | |
| V6B 100100 | 50 (122) |
| V6B 10030 | 50 (122) |
| V6B 10040 | 50 (122) |
| V6B 10060 | 50 (122) |
| V6B 10080 | 50 (122) |
| V6B 2525 | 50 (122) |
| V6B 2540 | 50 (122) |
| V6B 2580 | 50 (122) |
| V6B 40100 | 50 (122) |
| V6B 4025 | 50 (122) |
| V6B 4030 | 50 (122) |
| V6B 4040 | 50 (122) |
| V6B 4060 | 50 (122) |
| V6B 4080 | 50 (122) |
| V6B 60100 | 50 (122) |
| V6B 60120 | 50 (122) |
| V6B 6025 | 50 (122) |
| V6B 6030 | 50 (122) |
| V6B 6040 | 50 (122) |
| V6B 6060 | 50 (122) |
| V6B 6080 | 50 (122) |
| V6B 80100 | 50 (122) |
| V6B 80120 | 50 (122) |
| V6B 8025 | 50 (122) |
| V6B 8030 | 50 (122) |
| V6B 8040 | 50 (122) |
| V6B 8060 | 50 (122) |
| V6B 8080 | 50 (122) |

Marking: Company name or tradename "E197662", catalog or model number, the Recognized Component Mark,  and, if published with the product, the product's maximum and minimum operating temperature, minimum installation temperature if below 0°C, minimum and maximum bundle diameter, loop tensile strength, type designation and/or declared mechanical strength on the product or on the smallest unit container in which the product is packaged.

Last Updated on 2017-02-11

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

© 2018 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2018 UL LLC".